

PRODUCT SPECIFICATIONS

Feature Description	Model 1	Model 5	Model 10	Model 20	Model X2
<b>Platform</b>					
Desktop Hardware Appliance	Virtual Only	✓	✓	✓	-
Half Rack Hardware Appliance	-	-	-	-	✓
Virtual Appliance (Certified VMware-Ready)	✓	✓	✓	✓	✓
Number of Licenced Emulation Ports	2	2	2	4	4 (2 x 10G SFP+, 2 x 1G RJ45 Copper)
Maximum Link Speed (Bandwidth) / Packet Rate	50 Mbps / (3 Mpps)*	100 Mbps / (3 Mpps)*	200 Mbps / (3 Mpps)*	1 Gbps / (5.5 Mpps)*	10 Gbps / (44 Mpps)
BMC / IPMI Management Port	-	-	-	-	✓
UID Identifier Button	-	-	-	-	✓
<b>Network Links</b>					
Link Type: LAN, WAN, Wi-Fi, (A)DSL, 2G, 3G, 4G/LTE, 5G, Satellite, Custom	✓	✓	✓	✓	✓
Point-to-Point	✓	✓	✓	✓	✓
Dual hop (Single or Multi Link)	-	✓	✓	✓	✓
Multi-Link	-	✓	✓	✓	✓
Maximum Links	1	5	10	20	20
Link Congestion to mimic busy networks	✓	✓	✓	✓	✓
Bidirectional Link Configuration	✓	✓	✓	✓	✓
Queue Size (Buffer used when data rate exceeds transmission speed)	✓	✓	✓	✓	✓
Layer 2 Head Size	✓	✓	✓	✓	✓
Decrement Packet Time To Live (TTL/Hop Limit)	✓	✓	✓	✓	✓
Jumbo Frame Support	✓	✓	✓	✓	✓
<b>Built-In Intelligence &amp; Automation</b>					
Geolocation Network Latency Calculator	✓	✓	✓	✓	✓

Feature Description	Model 1	Model 5	Model 10	Model 20	Model X2
<b>Built-In Intelligence &amp; Automation (Continued..)</b>					
Database of more than 100 predefined networks, properties, types and conditions	✓	✓	✓	✓	✓
Network Scenario Builder & Player	-	-	✓	✓	✓
Command Line Interface	-	-	-	✓	✓
<b>Presentation, Usage &amp; Control</b>					
Intuitive Multi-User Web GUI including built-in hover-over help; manuals & video tutorials	✓	✓	✓	✓	✓
LCD Set Up & Control Panel (Desktop appliances only)	-	✓	✓	✓	-
Packet Capture on Ports or Links	✓	✓	✓	✓	✓
Graphs & Statistics Logging per link	✓	✓	✓	✓	✓
Multi-Tenanted	-	-	-	✓	✓
Connect unlimited users or test devices	✓	✓	✓	✓	✓
Save & Share Emulations & Scenarios	✓	✓	✓	✓	✓
<b>Value-Added Features &amp; Options</b>					
Full 1st Year Support & Maintenance included	✓	✓	✓	✓	✓
Upgradeable to higher spec. models via licence key	✓	✓	✓	-	-
Ruggedized Carry Case (Optional - Hardware Appliances only)	-	✓	✓	✓	N/A
<b>Network Impairments</b>					
Listed below are the principal impairments the NE-ONE can recreate. Each of these are further customizable to enhance the realism of your test setup					
<b>Latency &amp; Jitter</b>					
Gaussian (Normal Distribution) Delay	✓	✓	✓	✓	✓
Step Delay Periodic	✓	✓	✓	✓	✓
Step Delay Packet	✓	✓	✓	✓	✓
Fixed Delay	✓	✓	✓	✓	✓

Feature Description	Model 1	Model 5	Model 10	Model 20	Model X2
<b>Latency &amp; Jitter (Cont.)</b>					
Fixed Delay with Jitter	✓	✓	✓	✓	✓
Random Delay	✓	✓	✓	✓	✓
Inter Packet Gap	✓	✓	✓	✓	✓
<b>Loss</b>					
Random Loss with Burst	✓	✓	✓	✓	✓
Poisson Drop	✓	✓	✓	✓	✓
Packet Error - 1 in X bits	✓	✓	✓	✓	✓
Burst Loss	✓	✓	✓	✓	✓
Drop - 1 in X	✓	✓	✓	✓	✓
Random Drop	✓	✓	✓	✓	✓
<b>Duplicate</b>					
Packet Duplicate & Move	✓	✓	✓	✓	✓
<b>Out of Order</b>					
Random Packet Time Reorder	✓	✓	✓	✓	✓
Random Packet Move Offset	✓	✓	✓	✓	✓
Packet Reorder 1 in X	✓	✓	✓	✓	✓
<b>Fragment</b>					
Fragment MTU	✓	✓	✓	✓	✓
<b>Bit Error</b>					
Error with Burst	✓	✓	✓	✓	✓
Poisson Error	✓	✓	✓	✓	✓
Random Packet Error	✓	✓	✓	✓	✓
<b>Scenario Builder Network Transitions</b>					
<b>Gradual</b> - Changes parameters gradually (linearly)	-	-	✓	✓	✓
<b>Variable</b> - Changes parameters randomly	-	-	✓	✓	✓
<b>Outage</b> - creates an increasingly lossy network, followed by total loss, then comes back quickly but not instantly	-	-	✓	✓	✓
<b>Certification</b>					
<b>FCC/CE Certified</b> (Hardware appliances only)	-	✓	✓	✓	✓
<b>VMware Ready Certified</b> (Virtual appliances only)	✓	✓	✓	✓	✓

\* Exceeds packet rate required to be line rate for all packet sizes for licensed bandwidth.